LAND BASED DRILL LINE SPOOLERS

INNOVATIVE FLEXIBLE MATERIAL SPOOLING & COILING SOLUTIONS

Safety

Tulsa Power has worked closely with drilling contractors and rig manufacturers to specifically design and manufacture Drill Line Spoolers that will improve your operator's SAFETY and REDUCE cycle TIME.



TUAF-30 Hydraulic

PO

WE

R

Tulsa Power's Drill Line Spoolers are available for 3,000' of ³/₄" to over 10,000' of 2" drilling line.






Features:

- Powered Drill Line Spoolers greatly increase safety by preventing over-run and taking up slack
- Controllable speed and torque offer increased safety and efficiency
- Removable shaft allows for quick and easy reel change out
- Rotating/Drive components are well guarded for added operator safety
- Heavy-duty seal welded frame ensures durability and long life in oil-field environments
- Pad eyes and/or forklift pockets are available for moving ease

Options:

- Automatic levelwind
- On-board winch for ease of string-up/string-down
- Operator platform for added operator safety
- Tail-boardable for faster rig moves
- Heavy-duty reel(s) specifically designed for storing drill line
- Rewind service (wind drilling line onto spooler/reel prior to shipping) provided by Tulsa Power
- API carbon steel drill line





913 N. Wheeling | Tulsa, OK 74110 U.S.A. Toll Free: 800.548.6227 | Fax: 918.584.3421 sales@tulsapower.com | tulsapower.com

LAND BASED DRILL LINE SPOOLERS

INNOVATIVE FLEXIBLE MATERIAL SPOOLING & COILING SOLUTIONS

EXPERTISE

Tulsa Power has over 35 years of experience in designing and manufacturing Spoolers. Oilfield products include: Drill Line Spoolers, Wireline/Slickline Units, Truck and Trailer Mounted Spoolers, ESP Spoolers, Coiled Tubing Spoolers, Service Loop Spoolers, Seismic Cable Spoolers and Linear Hauloffs/ Cable Tensioners. Equipment can be designed and built for almost any spooling application.

TUAF-10 Pneumatic



TUAF-20 Hydraulic



Tulsa Power has the team and engineering excellence to accomplish any of your needs for customized equipment. All of our professionals (mechanical and electrical engineers) are on staff in our Tulsa, OK facility.

UNITS	DRILL LINE		REEL CAPACITY		TOTAL WEIGHT
MODEL	SIZE in. (mm)	LENGTH ft. (km)	MAX. FLANGE DIAMETER in. (m)	MAX. OUTSIDE WIDTH in. (m)	APPROX. LOADED lbs. / kg
TUAF-10	1 (25.4)	5,000 (1.5)	60 (1.5)	42 (1.1)	15,000 / 6,803
TUAF-20	1 1/8 (28.6)	5,000 (1.5)	80 (2.0)	55 (1.4)	16,600 / 7,530
TUAF-30	1 3/8 (34.9)	7,500 (2.3)	90 (2.3)	62 (1.6)	34,200 / 15,513
TUAF-45	1 3/4 (44.5)	7,500 (2.3)	100 (2.5)	70 (1.8)	55,500 / 25,174

Dimensions and weights are approximate and subject to change; dimensions for non tail-boardable unit. Reels offered as optional. Forklift pickets are not standard on sizes above TUAF-45-DLS. Other sizes available upon request.

