Deepwater Reels

Umbilical & Control Reels



Lower Your Operating Costs & Improve Safety

Trusted Partner – Reel Power has manufactured more Umbilical Reels than anyone in the World.

Patented Adjustable Fleet Angle allows greater flexibility in locating equipment and more accurate sheave alignment.

Patent Pending "Smart Reel" Constant Tension prevents damage to cable and equipment, never exceeding the riser speed.

Patented Slip Clutch Safety Feature Prevents Damage to the Cable and Equipment.

Patent Pending Power Brake Assist reduces air response time of braking. **Powered Level-wind Adjustment** gives easy access to correct level-wind on the fly.

Available for up to 13,500ft

REELS TYPES & COMMON USES

- Deepwater BOP Control MUX
 (Multiplex) –Electric and/or Fiber
 Optic Cables
- » Hotline Hydraulic Hose
- » Multifunction Hydraulic (POD)
- » IWOCS
- » Dual Gradient
- » Riser Fill Hydraulic Hose
- » Gas Handler
- » Annulus
- » Discreet



Reel Power has produced umbilical reels for almost every deepwater application.

Reel Power has developed many patented and patent pending features that improve the reliability and safety of the umbilical deployment and Lower the Operating Costs of the user.

Our **Smart Reel Constant Tension (CT-2)** (Patent Pending) system controls the motor and slip clutches to maintain a constant tension on the umbilical whether the reel is full or near empty. The smart system also prevents the reel from deploying faster than the riser.

The patented **"Banana Curve" Adjustable Angle Level-wind** allows the fleet angle to be adjusted within a 110o range allowing umbilical deployment from the vertical to just below the horizontal position. This allows greater flexibility for placing the reels on the vessel.

The **Power Brake Assist** (Patent Pending) system reduces the brake response time and allows better control of the brakes at I ower supply air pressure.

The patented **Slip Clutch** allows the spool to deploy umbilical even if the brakes are locked, protecting the umbilical and sheave from damage in the event of unexpected riser movement.

The control system allows the user to operate the reels locally or from a remote control panel or both (optional).

Features, Specs & Options:

- » Adjustable Level-wind Fleet Angle
- » Smart Reel Constant Tension
- » Slip Clutch Safety Feature
- » Available for up to 13,500 ft of umbilical
- » High Pressure Hydraulic Swivels
- » Electric and Fiber Optic Slip Rings
- » Explosion Proof Controls

- » Balanced and/or Light Weight Spools
- » Umbilical Sheaves (meet or exceed API 16D)
- » Umbilical Riser Clamps
- » Remote Control Panels
- » Spare Parts Kits
- » Umbilical Rewind Service







